WACOLL CAT. AS 6

Health Department, District of Columbia.

### REGULATIONS

GOVERNING

# Plumbing, House Drainage,

AND THE

Ventilation of House Sewers,

IN THE

DISTRICT OF COLUMBIA.

WASHINGTON, D. C.:
JUDD & DETWEILER, PRINTERS.



Health Department, District of Columbia.

### REGULATIONS

GOVERNING

## Plumbing, House Drainage,

AND THE

Ventilation of House Sewers,

IN THE

DISTRICT OF COLUMBIA.

WASHINGTON, D. C.:
JUDD & DETWEILER, PRINTERS.

1883.



#### REGULATIONS.

[Act authorizing the employment of an Inspector of Plumbing in and for the District of Columbia, and for other

Be it enacted by the Senate and House of Rep- Authorizing appointment of In-resentatives of the United States of America in spector, and execu-tion and enforce-Congress assembled, That there shall be ap-ment of regulapointed by the Commissioners of the District of Columbia an Inspector of Plumbing for said District, whose duty it shall be to inspect all houses in course of erection, and pass upon the plumbing and sewerage of said houses. And the Health Officer of the District of Columbia is hereby authorized, under direction of the Commissioners, to execute and enforce regulations governing plumbing, house drainage, and the ventilation of house sewers; and any person who shall neglect or refuse to comply with the requirements of the said regulations when promulgated shall be punishable by a fine of from twenty-five to two hundred dollars for each and every such offense, or in default of payment of fine to imprisonment for thirty days.

Approved January 25, 1881.

In accordance with the foregoing act of Congress, and in pursuance of authority thereby conferred, the following amended regulations are made and promulgated for the information and guidance of all concerned:

Regulations to take effect.

SEC. 1. These regulations governing plumbing, house drainage, and the ventilation of house sewers, shall take effect and be in force in the District of Columbia from and after December 1, 1882, and all work of the character named, thereafter placed in or about any structure in the said District shall be done in accordance with the provisions of the same.

Duties of Inspector of Plumbing.

SEC. 2. It shall be the duty of the Inspector of Plumbing, under direction of the Health Officer, to sign and issue all notices and certificates, to keep a daily record of his work, including all notices and applications received, violation of these regulations, and all other Reports to be matters which may pertain thereto; to make

made.

daily, weekly, and quarterly reports, and an annual report of his operations to the Health Officer.

Houses to be inspected.

SEC. 3. He shall inspect all houses in course of erection, alteration or repair, as often as may be necessary, and shall see that all plumbing, drainage, and sewerage work is done in accordance with the provisions of these regulations.

Oath to be taken and bond entered

SEC. 4. He shall take and subscribe an oath or affirmation that he will faithfully perform the duties of his office, and shall, before entering upon its duties, execute a bond to the District of Columbia in the sum of five thousand dollars, with three sureties, to be approved by the Commissioners, conditioned upon the faithful performance of the duties of his office, and for the benefit of all persons aggrieved by his acts or neglect.

Sec. 5. It shall be the duty of every person Plumbers to be bonded, registered, doing business as a plumber, or engaged in and display a sign. conducting plumbing or house drainage in the District of Columbia, to register his or her name in a book to be provided for that purpose at the Health Department, giving full name, residence, and place of business, and in case of removal from one place to another, in said District, to make change in said register accordingly, and it shall be the further duty of every such person to give good and sufficient bond in the sum of five hundred (500) dollars, to be approved by the Commissioners of the District of Columbia, conditioned upon the observance of these regulations.

It shall be the duty of every such person to display at his or her place of business in a conspicuous place a sign with full registered name and words 'Registered Plumber," in letters not less than three inches in size.

SEC. 6. Before any portion of the drainage Plan of plumbing system of any building shall be laid or con-work to be filed at Health Departm't. structed there shall be filed by the owner with the Health Officer, for the Inspector of Plumbing, a plan thereof showing the said drainage system entire from its connection with the main sewer to terminus in house, together with the location of all traps, ventilating pipes, &c. The name of the plumber who is to perform the

work shall be given on said plan, which must be approved by the Inspector of Plumbing before any portion of the work shall be executed. A permit shall not be given for the erection of any building until said plan shall have been presented and approved.

Permit required in all cases.

SEC. 7. No house or premises will be allowed to be connected with water, sewer, or gas main without a permit first obtained from the Engineer Commissioner. The conditions of this permit must be strictly complied with, and the work must be done by the plumber in whose name the permit is given.

This regulation applies to all sewers, whether on private property or in public streets or alleys.

Plumbers to notify the Engineer Commissioner of alterations, &c.

All plumbers are required to notify the Engineer Commissioner of any and all extensions or alterations of water fixtures and pipes made inside of buildings, so that the same may be examined

Applications and

SEC. 8. Blank forms of application will be blank forms to be signed by owners. furnished to plumbers. All applications must be signed by the owner of the premises, and his address written under his signature. Signing by agents will not be accepted if the owner resides in the District of Columbia.

Fee required.

SEC. 9. One dollar is required by law to be paid as permit fee for each house connected, the receipt of which must be endorsed upon the application; the fee to be paid to the collector of the District of Columbia.

SEC. 10. All connections with sewer must be Inspection to be made before trench inspected by the Sewer-tapper before the trench is filled. is filled, whether the service pipes have been run to the building line or not, and all appointments must be made when the permit is issued.

Sewer pipes, or main drains are not to be raised or lowered, or otherwise changed, except lowed except upon under the inspection of the Sewer-tapper, and permit. by permit from the Engineer Commissioner. Tunnelling is prohibited. All connections with pipe sewers must be made with Y branches. made. In every case where connection with brick sewers is made a terra-cotta junction block must be used. Branches and junction blocks, and all other material for use in or about the public sewers must be purchased from the District.

Connections how

SEC. 11. Pipe sewers must not be cut, nor to be cut. Connecany connections be made in any manhole, trap, with manhole trap or lateral. Each house must be drained by a or trap lateral. separate drain not less than six inches in diameter, having a fall of not less than one in forty, separately drained. Fall required. laid (inside the building line) entirely within the lot to which it belongs, and connecting outside the building line, only with that part of the system of drainage intended for it as shown on the general plans of sewerage on file in the office of the Engineer Commissioner. If this drain pipe be of terra-cotta it must be laid upon a foundation of hydraulic cement concrete four inches in thickness.

Pipe sewers not

Each house to be

SEC. 12. All concrete pavements must be re-concrete pavements to be repaired by the contractor doing such work for paired by contractor

tor, and granite the District Government, and all granite block by Superintendent pavements by the Superintendent of Repairs, of Repairs. at rates to be fixed by the Commissioners. Persons desiring to remove said concrete or granite block pavements must first deposit Deposit to be with the chief clerk of the Engineer's Depart-

made for removal of pavements.

ment the estimated cost of repairing the same, the receipt for which must be exhibited before the permit is issued. After the completion of the work the surplus, if any, will be returned.

Valves to prevent necessary.

SEC. 13. All permits for tapping sewers are back flows to be used whenever given on conditions that owners take all risk of damages that may result from water setting back into premises from the main sewers, and in order to prevent as much as possible the setting back of water the owner shall be required, at his own cost, to put in a self-acting or other valve in all cases where the back-flow from a sewer is to be apprehended; and it shall be the duty of the owner to keep the valve in order, and he must be responsible for its action in all cases. When the sewer connection is of iron, and carried up within the premises as a close pipe, without opening or connections of any kind, above the level of all back-flow, the flood-valve may be dispensed with, being unnecessary.

Time allowed for filling trench, &c.

SEC. 14. The trench must be filled up, thoroughly puddled and rammed within forty-eight (48) hours after making the connection, and the pavement relaid not less than twenty days after filling, all in a workmanlike manner, satisfactory to the District Commissioners, so that no settling will occur. All rubbish must be removed from the street on completion of the work.

SEC. 15. A running trap shall be placed on drain. Trap on main every main drain at an accessible point, and a man-hole, with suitable iron cover, shall be constructed over the trap to admit of cleaning the same.

Sec. 16. Every main drain shall have an Main drain to be inlet for fresh air entering on the house side of trap, and carried to such point as may be approved by the Inspector.

SEC. 17. When necessary to lay a soil pipe der buildings under a building, such pipe shall be of iron with leaded joints, and shall be so located as to be readily accessible for inspection. Such pipes shall be kept above ground, if practicable, shall be not less than four (4) inches in diameter, and shall extend above the roof of house; this extension shall be at least four (4) inches in diameter.

SEC. 18. Where pipe passes under walls of Relieving arch house there shall be a relieving arch to prevent settling of walls. pipe being broken by settling of brick work.

SEC. 19. The weight of all iron pipe used Weight of iron under ground shall be not less than—

For six-inch pipe, 20 pounds per lineal foot.

For five-inch pipe, 17 "

For four-inch pipe, 13 "

For three-inch pipe,  $9\frac{1}{2}$  "For two-inch pipe,  $5\frac{1}{2}$  "

Pipe to be coated with coal tar.

SEC. 20. All iron, soil, and sewer pipes shall be coated inside and outside with coal tar ap-Changes of direc-plied hot. All changes in direction shall be

tion.

made with curved pipes, and all connections Connection of with Y branches and one-eighth bends. All

lead with iron pipe.

connections of lead with iron pipes shall be made with brass thimbles, full size of iron pipe, caulked into the iron with lead, and plumbers' wiped joints.

Sub soil drains to be provided.

SEC. 21. Sub soil drains shall be provided whenever dampness of site of any proposed dwelling is known to exist. These may be of terra-cotta, not connected with sewers, but discharge into a manhole over running traps, and have a back water valve.

Vaults, sinks and cess pools not to be drainage system.

SEC. 22. No vault, sink, cesspool or drywell connected with shall be in any way connected with the drainage system of any house, and all vaults, sinks, or cesspools must be water tight.

Rain-water leaders, &c.

SEC. 23. Rain-water leaders when placed inside of any house shall be of iron with leaded or screwed joints; and when opening below or near any windows shall be effectually trapped.

Flue not to be used as ventilator.

SEC. 24. No brick, sheet-metal, or earthenware flue shall be used as a sewer ventilator, or trap vent.

Pipes to be concentrated.

SEC. 25. All soil, drain, waste and supply pipes shall be concentrated as much as possible, protected from exposure to frost, and shall be so located as to be readily accessible for inspection.

SEC. 26. Every soil, drain, or waste pipe in- Soil and drain pipes to be of iron. side of the building line and five (5) feet exterior thereto, shall be of iron.

SEC. 27. No trap shall be placed on or at No traps on vertical soil pipes. the foot of vertical soil pipes so as to impede circulation of air.

SEC. 28. All water-closets, sinks, basins, wash When traps shall trays, &c., shall have suitable and approved be used. traps placed as near as practicable to said fixtures.

SEC. 29. Each and every trap shall have a Ventilation of special vent pipe of iron, extending either above the roof of house, or into the soil pipe above the highest fixtures.

SEC. 30. The vent pipe for each water-closet Size of vent pipe. trap shall be not less than two (2) inches in diameter, and for traps under other fixtures not less than one and one-fourth inches; but if exceeding ten (10) feet in length this pipe shall be not less than one and one-half (14) inches in diameter.

SEC. 31. Waste pipes from bath tubs, washstands, and sinks shall not be connected with waste from baththe trap of a water-closet.

Connection of tubs, wash stands, and sinks.

SEC. 32. There shall be no direct connection No direct conof water-closets above basement floor with ser-nection of water-closet with service vice pipe. pipe.

Flushing to be SEC. 33. Means for thorough flushing of all secured.

soil pipes, drain pipes, and water-closets shall be provided in every case.

Tanks or eisterns to be used when necessary.

SEC. 34. Where water supply is not ample for proper flushing of water-closets, &c., the Inspector of Plumbing may, in his discretion, order the erection of a tank or cistern into which water may flow at night, or into which it may be pumped.

Supply for dotern.

SEC. 35. Cisterns or tanks erected for purmestic purposes not to be drawn poses described in the foregoing paragraph from tank or cisc shall not have an avend an appropriate with shall not have an overflow pipe connected with any drain, and water supply for domestic purposes shall not be drawn therefrom.

Safes, and refrigcrators to be specially drained.

Sec. 36. All safes and refrigerators shall be drained by special pipes not directly connected with the house drain or main sewer.

Wooden washtrays, and sinks prohibited.

SEC. 37. Wooden wash-trays and sinks are prohibited inside of buildings; they shall be of non-absorbent material.

Notification to be given by the plum-ber in writing.

Sec. 38. The Inspector of Plumbing shall be notified promptly in writing by the plumber, and upon blank forms to be provided for that purpose, when the plumbing work on any house is completed and ready for inspection. All inspections shall be made as soon as possible after such notification, and the pipes shall be tested by filling with water. No part of the plumbing work of any house shall be covered, or in any manner hidden from view until after such inspections shall have been made, and a certificate of approval issued by the Inspector.

Work to remain exposed until after approval.

SEC. 39. The Inspector shall promptly con-and material to be demn and order the removal of any defective condemned. material, or of any work done other than in accordance with the provisions of these regulations.

SEC. 40. Prosecution for infringement upon the provisions of these regulations shall be made by information filed in the Police Court in the District of Columbia.

SEC. 41. These regulations shall be subject Amendments, we. to alteration or amendment at any time.

SMITH TOWNSHEND, M. D., Health Officer, District of Columbia. Approved.



OFFICE OF THE COMMISSIONERS,
DISTRICT OF COLUMBIA,
WASHINGTON, November 17, 1882.

Order.

Ordered:

That the above amended regulations are approved; and it is further required that permits shall be kept at hand during the progress of the work, to which they relate, and that they shall be exhibited whenever required by the proper officers of the District. The police are instructed to arrest any one found making any excavation in the streets or making any sewer connection without permits, as required by the foregoing regulations.

J. R. West, Thos. P. Morgan, G. J. Lydecker,

Major of Engineers, U. S. A., Commissioners of the District of Columbia.





